

# Chemicals contained in products

## Package-type

Epson Package name; **VF8GA8H-81 / Halogen free**

JEITA Package name; **P-VF8GA-081-0808-0.80**

Solder ball Type; **Lead(Pb) Free**

Weight; **0.10 [g] \*Note1**

Part	Subpart	Subpart weight [mg]	Substance name	CAS No.	Content ※2		Application		
					[mg]	[ppm]			
チップ	ICチップ	3.9	Silicon	7440-21-3	3.9	999914	Base material		
			Boron	7440-42-8	0.00001	2	Dopant		
			Phosphorus	7723-14-0	0.00002	5	Dopant		
			Aluminum	7429-90-5	0.0001	20	Metalization		
			Arsenic *Note3	7440-38-2	0.00002	5	Dopant		
			Fluorine *Note3	7782-41-4	0.00001	2	Dopant		
			Titanium *Note3	7440-32-6	0.0001	20	Metalization		
			Tungsten *Note3	7440-33-7	0.0001	30	Metalization		
			Cobalt *Note3	7440-48-4	0.00001	2	Metalization		
PKG	保護膜	0.08	Polyimide	-	0.08	1000000	Stress buffer coat *Note4		
			Glass-cloth	-	4.70	175310	Reinforcement		
	回路基板	26.4	Barium Sulfate	7727-43-7	1.00	40790	Additive		
			Epoxy resin	-	5.20	197180	Base material		
			Acrylate resin	-	1.50	57800	Base material		
			Pigment	-	0.68	25520	Additive		
			Organic filler	-	0.09	3400	Filler		
			Zinc	7440-66-6	0.02	920	Characteristic preserve		
			Chromium	7440-47-3	0.001	30	Characteristic preserve		
			Copper	7440-50-8	11.10	419050	Copper foil		
			Nickel	7440-02-0	1.70	64000	Plating		
			Gold	7440-57-5	0.43	16000	Plating		
			ダイアタッチ材	1.81	Epoxy resin	-	1.20	670000	Adhesive
					Acrylic resin	-	0.61	330000	Adhesive
			半田ボール	16.18	Tin	7440-31-5	15.50	957500	Solder ball
					Silver	7440-22-4	0.56	35000	Solder ball
	Copper	7440-50-8			0.12	7500	Solder ball		
	ボンディングワイヤー	1.40	Gold	7440-57-5	1.40	1000000	Conductor		
			Epoxy resin	-	2.50	50000	Base material		
	モールド樹脂	50.12	Silica	60676-86-0/-	43.80	873000	Filler		
			Carbon black	1333-86-4	0.10	2000	Coloring agent		
			Hardening chemical(ex:Phenol resin)	-	2.50	50000	Base material		
			Organic phosphorous compound	-	0.25	5000	Hardening accelerator		
			others	-	0.97	20000	Additive		

Regarding the information of chemical substances

\*Note1 The weight might be somewhat different depending on an individual built-in IC-chip specification like the size etc.

\*Note2 Content data are estimated values based on supplier information and intended levels of content in product.

Actual measurements may vary from these values somewhat.

\*Note3 Use or not-use of these substances depends on individual built-in IC-chip specification.

\*Note4 The stress buffer coat may not be used depending on the individual model.